

**Whatever your cleaning requirements are
We've got you covered...**



Stainless Steel High-Performance



Stainless Steel with Trolley



Stainless Steel Top loader



Heavy Duty & Mine Spec



Stainless Steel Hot Manual Washers



Heavy Duty cold-solvent Manual Washers



Hot Blast Cabinets



Wet Abrasive Blast Cabinets

The Hotwash Range

- ✓ S/Steel automatic parts washers
- ✓ Heavy duty automatic parts washers
- ✓ S/Steel manual parts washers
- ✓ Heavy duty manual washers
- ✓ Hot blast cabinets
- ✓ Wet abrasive blast cabinets
- ✓ Cleaning chemicals



Stainless Steel with Sliding Door

Hotwash has the biggest range of parts washers in Australia. No matter how large or small your requirements are, we will meet them and make your life easier.

BUY – RENT - FINANCE

Talk to one of our consultants and see what they can do to tailor a deal that suits your needs **and** your budget. Hotwash has parts washers from as small as a 55cm basket to as large as a 1.85m basket, catering to almost any cleaning job in most every workshop. *Put us to the test and see for yourself*

283 Treasure Rd North, Welshpool, Perth WA

Call: 1800 644 378

e-mail: sales@hotwash.com.au

web: hotwash.com.au

STAINLESS STEEL SPECIFICATIONS

TECHNICAL SPECIFICATIONS	MODEL SS550	MODEL SS720HP	MODEL SS870HP	MODEL SS1100-T	MODEL SS1100-HP	MODEL SS1350-HP	MODEL SS1350-SD	MODEL SS1600-SD	MODEL SS1850-SD
Basket Diameter (mm)	550	720	870	1100	1100	1350	1350	1600	1850
Internal Height (mm)	275	350	450	440	750	950	650	800	900
Tanks Capacity (Ltrs)	50	75	100	175	175	300	300	300	300
Pump Pressure (Bar)	2.2	2.5	2.5	3	3	3	3	9	9
Pump Qty & Power	1 x 0.37kw	1 x 0.9kw	1 x 1.5 kw	1 x 2.2kw	1 x 2.2kw	1 x 2.2kw	1 x 3.0kw	2 x 3.0kw	2 x 3.0 kw
Heater Elements (kw)	5.0 kw	7.5 kw	7.5 kw	15 kw	15 kw	15 kw	15 kw	15 kw	22 kw
Loading Weight (kg)	100	150	300	440	750	950	650	650	650
Power (V/phase)	240/1	240/1	415/3	415/3	415/3	415/3	415/3	415/3	415/3
Timer (mlns)	0 - 30	0 - 30	0 - 30	0 - 30	0 - 30	0 - 30	0 - 30	0 - 30	0 - 30
Thermostat (Deg C)	0 - 65	0 - 65	0 - 65	0 - 65	0 - 65	0 - 65	0 - 65	0 - 65	0 - 65
Stainless Steel Body	AISI 304	AISI 304	AISI 304	AISI 304	AISI 304	AISI 304	AISI 304	AISI 304	AISI 304
Machine Foot Print	85 x 93 x 98	123 x 88 x 107	141 x 104 x 114	166 x 129 x 140	166 x 129 x 140	200 x 175 x 200	220 x 190 x 200	220 x 190 x 200	220 x 220 x 220
Min effective spray distance (cm)	40	50	50	50	50	55	55	65	75
Machine Weight (kg)	85	125	180	360	360	680	680	900	1000
Total Max Current Rating (amps)	20amp, 1ph	20amp, 1ph & 3ph	20amp, 3ph 4pin	32amp, 3ph 4pin	32amp, 3ph 4pin	32amp, 3ph 4pin	52amp, 3ph 4pin	63amp, 3ph 4pin	80amp, 3ph 4pin
Loading Trolley	-	-	-	✓	-	-	✓	✓	✓
Turntable with driving motor	✓	✓	✓	✓	✓	✓	✓	✓	✓
High Performance	-	✓	✓	-	✓	-	-	-	-
Liquid Level Control	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Auto Water Top Up	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard

HEAVY DUTY SPECIFICATIONS

MODEL	HW1100G	HW1400G	HW1600G
Turn Table Diameter	1100	1400	1600
Internal Height (mm)	550	700	800
Load Capacity (kg)	750	1000	1250
Height (Lid closed)	1205	1520	1620
Width	1400	1950	2250
Depth	1290	1780	2100
Weight (kg)	450	550	650
Pump Motor (kw)	4	5.5	7.5
Tank Capacity (Ltrs)	275	400	500
Heating Elements	3 x 3.6KW	3 x 3.6KW	3 x 4.2KW
Connection	32 amp, 4Pin	32 amp, 4Pin	32 amp, 4Pin
Stainless Steel Construction	Optional	Optional	Optional
3 Phase	✓	✓	✓
Turn Table Drive	Gear Drive	Gear Drive	Gear Drive
Cycle Timer	✓	✓	✓
IP65 Electrics	✓	✓	✓
Spray Bar Flush	✓	✓	✓
Water Top Up	✓	✓	✓
Low Water Cut Out	✓	✓	✓